





Competitor Feature Cross Reference

Brand		Metalumen	Cooper Lighting Corelite	GE	Lunera	Ledalite
Product Name		Horizon II O5K/O5B	Divide Suspended	Lumination Series	Series L7	Boldplay
Product Image						
General Characteristics	Cross section Dimensions (width X Height)	12" X 2.9"	12" X 2.2"	11.8" X 1.38"	8" X 1.16"	9.4" X 1.67"
	Standard 4' Length	Yes	Yes	Yes	Yes	Yes
	Standard 8' Length	Yes	Yes	Yes	Yes	Yes
	Standard 12' Length	Yes	NO	NO	NO	YES
Lighting Characteristics	CRI	83+	82+	80+	84	84
	CCT	3000K, 3500K, 4000K	3000K, 3500K, 4000K	3000K, 3500K, 4000K	3500K, 4000K	3000K, 3500K, 4000K
	Lumen Package	O5K: 3079, 3924, 5621, 10775 O5B: 3230, 4119, 5898, 11304	3300, 4600, 5600, 7100, 8700	4200	3069	3399, 4767
	Input Watts	27W, 35W, 48W, 96W	31, 45, 57, 74, 94	55	44.7	32.2, 46.7
	Efficacy (LPW)	Up to 123	Up to 106	76	69	up to 106
	Dimming	0-10V Standard, DALI optional	0-10V Standard, DALI optional	0-10V Standard, DALI optional	0-10V	0-10V
	Driver Mounting	Integral or Remote	Integral or Remote	Remote Only	Remote Only	Integral
	Rated Life	60,000h	50,000h	50,000h	50,000h	60,000h
	Warranty	5 Years	5 Years	5 Years	5 Years fixture and LED, 3 Years driver	5 Years
Features	Direct/Indirect	Yes	Yes	Yes	Yes	Yes
	Integral Sensors	Yes	Yes	No	No	Yes
	Integral Battery	Yes	Yes	No	No	Yes