Metalumen

Ideas brought to light

Horizon II O5B& O5K LED LED . Pendant . Indirect/Direct





Architectural Commercial Lighting just got 123 LPW better with Horizon II LED series

Metalumen is pleased to announce the launch of the new and improved direct/indirect LED and fluorescent pendants, Horizon II O5K & O5B series. These revolutionary new products merge affordability and performance. Designed to complement almost any decor with clean lines and a slim profile, these fixtures will look at home in a high-end office environment or will modernize a utilitarian school. With up to 123 LPW luminaire in T8, T5 and T5HO equivalent, there is no reason you cannot meet and exceed outstanding energy conservation savings for your application.

Standard Features

- LED option features direct/indirect distribution, using our new and efficacious LED array and MetaLED mid flux LED technology optical system in conjunction with Metalce acrylic diffuser for smooth distribution; this creates a continuum of uniform light.
- Four LED light levels per model from 3079 to 11304 lumens •
- Up to 123 LPW •
- 4', 8', 12' sections or continuous runs •
- +65% savings including maintenance •
- Three CCT 3000K, 3500K & 4000K •
- Standard 0-10V dimming driver. •
- Optional Integral Daylight and occupancy sensor •
- 83+ CRI in LED •
- T8, T5, T5HO, or LED available. •
- Perforated or solid cross blade baffle •
- 120-277V or 347V
- LM79 & LM80 compliant •
- L85 @ 60,000h by TM21
- 5 year Limited warranty
- **DLC** pending qualifications

Wattage	Lumens Delivered		Efficacy (LPW)		Fluorescent Equivalent	Energy Savings*
	O5K	O5B	O5K	O5B		
27	3079	3230	113	118	2T8/T5	48%
35	3924	4119	113	118	2T8/T5HO	36%
48	5621	5898	118	123	3T8/2T5/T5HO	50%
96	10775	11304	113	118	3T5HO	46%
	27 35 48 96	Wattage OSK 27 3079 35 3924 48 5621 96 10775	Wattage O5K O5B 27 3079 3230 35 3924 4119 48 5621 5898 96 10775 11304	O5K O5B O5K 27 3079 3230 113 35 3924 4119 113 48 5621 5898 118 96 10775 11304 113	Wattage O5K O5B O5K O5B 27 3079 3230 113 118 35 3924 4119 113 118 48 5621 5898 118 123 96 10775 11304 113 118	Wattage Equivalent O5K O5B O5K O5B 27 3079 3230 113 118 2T8/T5 35 3924 4119 113 118 2T8/T5HO 48 5621 5898 118 123 3T8/2T5/T5HO

Up to 50%

Energy Savings

ONLY



Ideas brought to light

Horizon II LED

Marketing Collateral

For your convenience our website has been updated with new marketing material including a brochure, specification sheet and photometric files. <u>Click here</u> for more details.

In addition, a competitive analysis, FAQ Sheet and a PowerPoint presentation is posted to the agent portal to assist with your sales efforts. <u>Click here</u> to download these tools.

NPI Webcast

A New Product introduction webcast will be held to review the great features and benefits. An invitation will be sent out.

Pricing and Commission

Contact our quotations team for pricing on your latest project opportunity. A price list will be placed on the <u>Agent Portal</u>.

Thank you for your continued support.









Miraflor Romero Marketing Communications Coordinator John Bouls Strategic marketing Manager