Mounting Options TO-M4-03 STANDARD Aircraft Cable & Cord CONTRACTOR TO ATTACH FIXTURE STUD TO STRUCTURE OF SUITABLE STRENGTH TO SUPPORT FIXTURE SCREWS (BY OTHERS) 38 [1-1/2] DEEP OCTAGON BOX (BY OTHERS) 127 [5.0] Ø DISHED CANOPY (WHITE) Ш ***** 480 TO TOP OF [18.9] FIXTURE 18-4 STW WHITE POWER CORD (‡) (SUPPLIED 450 [18] LONGER CANOPY SUPPORT THAN SPECIFIED SUSPENSION LENGTH) **BUSHING** AIRCRAFT CABLE ADJUSTABLE CABLE HOLDER ±150 [6.0] FROM DIMENSION SHOWN NOTE BRACKET ORIENTATION Site installation must comply with national SUITABLE FOR SLOPED **CEILING APPLICATIONS** and local building and electrical codes. Notes Mounting height * Standard mounting height as shown above. Standard aircraft cable and power cord mounting detail. If a different height is required please indicate below Suitable for T-Bar and plaster ceiling applications. Junction box must be flush to ceiling. special height (‡) Some small profile series fixtures utilize 18-3 SVT for 120/277 volt. All dimensions are nominal and subject to tolerances. We reserve the right to make changes that will not alter installed appearance, function, or performance. These designs remain the property of Metalumen. We reserve the exclusive right to reproduce them and to manufacture the items illustrated herein. Some combinations may not be available, consult factory. Metalumen™ is a registered trade mark. © 2006 Metalumen Manufacturing Inc. R2-05-06 Approvals

11 Metalumen

570 Southgate Drive, Guelph, Ontario N1H 4P6
Mailing Address: P.O. Box 1779 Guelph, Ontario, N1H 6Z9
T: 800.621.6785 T: 519.822.4381 F: 519.822.4589
www.metalumen.com

Signature